

Hong Kong

Productivity  
Council

your most trusted partner since 1967

# Prototype Study of Biofilm Processes with Mobile Carriers for Sewage Treatment

by

Dr. Anthony MA

Principal Consultant

Environmental Management Division

DSD R&D Forum 2012

*Wastewater Treatment Session*


28 November 2012



Hong Kong  
Productivity Council  
香港生產力促進局<sup>1</sup>


- Introduction – Biofilm Processes
- Prototype Study
- Study Results
  - Comparison between FA and IFAS
  - Comparison between Treating Raw Sewage and CEPT Effluent
  - Comparison between IFAS and MBBR
  - Summary of Study Results
- Potential Application in HATS 2B

# Introduction – Biofilm Processes



# Introduction – Biofilm Media



- Fixed-bed Media



- Moving-bed Media



# Introduction – Biofilm Processes



- Microorganisms grow and develop on the surface of MBBR carrier (biofilm)
- Decomposition of organics take place in biofilm
- As biofilm grows thicker, it will slough off from the carrier and settled as sludge


# Introduction – Prototype Study

- CEPT effluent from the SCISTW needs further treatment under the HATS 2B to meet the future WQO
- In view of the space constraints in SCISTW, DSD has commissioned HKPC to evaluate the applicability and performance of biofilm processes with mobile carriers on treating the CEPT effluent
- The prototype reactors were housed in a 20-ft container in SCISTW
- The study was conducted between 12 Oct 2010 and 28 Jun 2012




# Schematics of Biofilm Reactors


- Fully-Aerated (FA) System – hybrid system without denitrification



- Integrated Fixed Film Activated Sludge (IFAS) – hybrid system with denitrification



- Moving Bed Biofilm Reactor (MBBR) System – pure attached-growth system




- To assess the effectiveness of using biofilm reactors to treat the CEPT effluent and raw sewage
- To operate the prototypes at stressed conditions so as to determine the maximum loading/shortest HRT that can be accepted by the biofilm reactors to meet generic effluent criteria:
  - $BOD_5 \leq 20 \text{ mg/L}$
  - $TSS \leq 30 \text{ mg/L}$
  - Ammonia-nitrogen  $\leq 5 \text{ mg/L @}18^\circ\text{C}$
- To assess the denitrification performance of the biofilm reactors (based on  $TN \leq 20 \text{ mg/L}$ )
- To estimate the sizes of the biofilm reactors for SCISTW for illustration



## System Parameters of FA, IFAS and MBBR

	FA	IFAS	MBBR
Volume of tank	150 L	150 L	150 L
Volume of anoxic zone	N/A	45 L (30%)	60 L (40%)
Volume of aerobic zone	150 L	105 L (70%)	90 L (60%)
Volume of carriers in anoxic zone	N/A	N/A	30 L (50%)
Volume of carriers in aerobic zone	90 L (60%)	63 L (60%)	59 L (65%)
Mobile carriers	AnoxKaldnes K3		
Specific biofilm surface area (in bulk)	500 m <sup>2</sup> /m <sup>3</sup>		
Biofilm surface area used in anoxic zone	N/A	N/A	15 m <sup>2</sup>
Biofilm surface area used in aerobic zone	45.0 m <sup>2</sup>	31.5 m <sup>2</sup>	29.5 m <sup>2</sup>
Range of Flow rate	400–1,700 L/day		
DO setting in aerobic zone	3 – 4 mg/L		





# Study Programme




# Comparison between FA and IFAS

# Comparison between FA and IFAS

- At moderate HRT (~6.5 hr), FA and IFAS could fully meet the effluent criteria of TCOD, TSS and NH<sub>3</sub>-N when treating both raw sewage and CEPT effluent at 23°C.



# Comparison between FA and IFAS



- 1) Hybrid **FA** system without pre-denitrification suffered from pH drop problem after nitrification when treating CEPT effluent
- 2) Hybrid system with pre-denitrification (IFAS) has the merits of TN removal and supplementation of alkalinity consumption and oxygen requirement
- 3) Limitation of **IFAS** – when the reactor MLSS is further reduced, *pre-denitrification performance may deteriorate.*

# Comparison between Treating Raw Sewage and CEPT Effluent


# Shorter Min HRT in CEPT Effluent at 23°C and 18°C

- Minimum HRT required for MBBR and IFAS to treat CEPT effluent were impressively short

Prototype System	Operating Temp.	Min. HRT (hr)		% Reduction in Min. HRT
		Raw Sewage	CEPT Effluent	
<b>IFAS</b>	23°C	4.2	→ 2.4	43%
	18°C	5.1 – 5.6	→ 3.1 – 3.2	39 – 42%
<b>MBBR</b>	23°C	6.2	→ 3.8	39%
	18°C	7.2 – 7.8	→ 4.5 – 4.9	38%



# Biomass Overgrowth under High Loading Rates of Raw Sewage



*Normal Condition*

*Biomass Overgrowth*

*Normal Condition*

*Biomass Overgrowth*



**MBBR**

**IFAS**

- Flourishing growth and thick layer of heterotrophic biomass
- Hinder oxygen from penetrating into the biofilm of nitrifiers
- Suppressed growth and activities of nitrifiers
- Poor ammonia removal performance
- Long restoration period


# Lower Organic Content in CEPT Effluent Favouring Ammonia-N Removal

- CEPT effluent had lower COD and BOD<sub>5</sub> contents but comparable levels of NH<sub>3</sub>-N and TKN as raw sewage
- When treating CEPT effluent, higher NLR could be achieved as corresponding OLR was not as high as on treating raw sewage.
- CEPT effluent was more favourable to higher NLR and shorter HRT.



# TN Removal of IFAS and MBBR on treating CEPT Effluent



- Effluent TN of IFAS and MBBR on treating CEPT effluent could comply with the effluent criteria of  $TN \leq 20$  mg/L, but not so good as treating raw sewage because of less carbon source to facilitate denitrification.




# Comparison between IFAS and MBBR

# COD and BOD<sub>5</sub> Removal

- Comparable and satisfactory treatment performance in COD and BOD<sub>5</sub> removal
- MBBR showed slightly better removal on COD and BOD<sub>5</sub>
- Both systems started deteriorating under very high loading conditions
- It took time for biomass acclimatization



Notes: The generic effluent criteria of BOD<sub>5</sub> ≤ 20 mg/L.




Notes: The generic effluent criteria of NH<sub>3</sub>-N ≤ 5mg/L.

- NH<sub>3</sub>-N removal was the limiting factor in treatment performance
- Low effluent NH<sub>3</sub>-N could be achieved under favourable operating condition
- NH<sub>3</sub>-N removal was impaired by biomass overgrowth or under stressed condition

- **To facilitate higher NLR and shorter HRT**
- Control OLR within acceptable level to avoid biomass overgrowth
- Separate nitrification from carbonaceous removal process (only applicable to MBBR)


# TN Removal and Effluent $\text{NO}_2\text{-N} + \text{NO}_3\text{-N}$

- Both IFAS and MBBR showed satisfactory denitrification performance. Effluent TN of both systems  $\leq 20\text{mg/L}$  so TN was *not a limiting factor*
- Effluent  $\text{NO}_2\text{-N} + \text{NO}_3\text{-N}$  of both systems was *higher* on treating CEPT effluent, showing better denitrification when treating raw sewage.



Notes: The generic effluent criteria of TN  $\leq 20\text{ mg/L}$ .

- **Effluent TSS of MBBR** was *better than* IFAS on treating either raw sewage or CEPT effluent.
- **MBBR** had more flexibility on final clarification due to much lower solid loading to the final clarifiers and no sludge return





Notes: The generic effluent criteria of TSS  $\leq$  30mg/L.




# MLSS and Sludge Settling Properties

- While  $SV_{30}$  of MBBR maintained at  $< 40$  ml/L when treating CEPT effluent,  $SV_{30}$  of FA and IFAS fluctuated between 100 – 1000 ml/L.
- IFAS suffered the occurrence of filamentous bacteria (**sludge bulking**) under high loading conditions.
- **Final clarification for IFAS** is *relatively difficult* and requires longer retention time.




# Minimum HRT of IFAS and MBBR

Minimum HRT achieved by IFAS and MBBR were governed by NH<sub>3</sub>-N removal efficiency




Prototype System	MBBR		IFAS	
	23	18	23	18
Operating Temp. (°C)	23	18	23	18
Raw Sewage	6.2	7.2 – 7.8	4.2	5.1 – 5.6
CEPT Effluent	3.8	4.5 – 4.9	2.4	3.1 – 3.2

# Biomass in IFAS and MBBR




Notes: MLSS controlled at 900 mg/L in IFAS from Phase 2 Part 4.

- 1) Substantial **attached growth biomass** for both IFAS and MBBR whereas the suspended biomass in IFAS was low.
- 2) MBBR carrier was *more susceptible to biomass overgrowth* under high OLR
- 3) MBBR had *greater biomass than* IFAS in anoxic zone. There might be room to further reduce the anoxic fraction in MBBR and in turn reduce the HRT.



# Relative Amount of Nitrifiers

- Nitrifier population concentrated on biofilm carriers in aerobic zone for both systems.
- When treating CEPT effluent, MBBR actually had more nitrifiers than IFAS, but lower nitrification efficiency



Relative amount of nitrifiers in the biomass of MBBR and IFAS determined by qPCR analysis carried out by the research team of Dr. T. Zhang, Department of Civil Engineering, The University of Hong Kong.

- The lower nitrification efficiency in MBBR than IFAS might possibly due to:
  - For **MBBR** under high OLR, **heterotrophic biomass grew excessively** on top of the autotrophic biomass on the mobile carriers, the biomass overgrowth could have **affected DO penetration and substrate diffusion** to the nitrifiers and impaired the nitrification activity;
  - For **IFAS**, the **influent COD** was first **removed by the suspended growth biomass** in both anoxic zone and aerobic zone of the IFAS reactor, so there was **less adverse effect of “biomass overgrowth”** on the nitrification.

# Summary of Study Results

1. At moderate HRT (~6.5 hr), IFAS could fully meet the effluent criteria of BOD, TSS, NH<sub>3</sub>-N and TN when treating both raw sewage and CEPT effluent at 23°C.
2. FA system suffered from pH drop problem when treating CEPT effluent whereas hybrid system with pre-denitrification (IFAS) had the merits of TN removal and supplementation of alkalinity consumption and oxygen requirement.
3. Minimum HRT of IFAS and MBBR on treating raw sewage and CEPT effluent (governed by ammonia removal) at 23°C and 18°C were impressively short

Prototype System	Operating Temp.	Min. HRT (hr)	
		Raw Sewage	CEPT Effluent
<b>IFAS</b>	23°C	4.2	2.4
	18°C	5.1 – 5.6	3.1 – 3.2
<b>MBBR</b>	23°C	6.2	3.8
	18°C	7.2 – 7.8	4.5 – 4.9

4. When treating raw sewage under high loading, biofilm carriers are susceptible to biomass overgrowth. CEPT effluent has lower organic content but comparable nitrogen content as raw sewage. This led to lower organic loading rate (OLR), favouring higher nitrogen loading rate (NLR) and shorter HRT.
  
5. IFAS and MBBR have comparable and satisfactory performance:
  - Both systems showed satisfactory denitrification performance
  - IFAS had shorter minimum HRT governed by  $\text{NH}_3\text{-N}$  removal efficiency
  - MBBR showed better COD and  $\text{BOD}_5$  removal
  - MBBR had much lower solid loading to final clarifier and better sludge settling properties, resulting in better effluent TSS

# Potential Application in HATS 2B




# Potential Application in HATS 2B (5 Options)




- A two-level basement, each level with a maximum floor area of about 130,000 m<sup>2</sup>, will be designed for the additional secondary treatment for the HATS 2B. The average dry weather flow (ADWF) is about 2,441,000 m<sup>3</sup>/d in HATS 2B.
- Only the areas for the biological reactors and final clarifiers are considered.
- The space requirement of other auxiliary equipment, like pumps, air blowers, sludge handling, odour control system and other facilities, has not yet been taken into account.
- Based on the minimum HRT for IFAS and MBBR to treat CEPT effluent and raw sewage at 18°C.

# Design Options for CEPT Effluent


## Option 1 – IFAS Option



## Option 2 – MBBR Basic Option




## Option 3 – MBBR Improved Option




# Design Options for Raw Sewage

## Option 4 – IFAS Option



## Option 5 – MBBR Option



# Footprint of IFAS and MBBR Options

Influent		CEPT Effluent			Raw Sewage	
Option		Option 1	Option 2	Option 3	Option 4	Option 5
	Unit	IFAS Option	MBBR Basic Option	MBBR Improved Option	IFAS Option	MBBR Option
Hydraulic Retention Time of Biological Reactors (Duty)	hr	3.11	4.49	3.35	5.11	7.20
<b>Estimated floor area of Reactors (including access for maintenance)</b>	m <sup>2</sup>	65,200	94,200	70,200	107,100	151,000
<b>Estimated floor area for Final Clarification (including access for maintenance)</b>	m <sup>2</sup>	129,600	60,000	60,000	129,600	Use existing CEPT Plant

- Based on the study results, five design options have been developed for HATS 2B for comparison. In view of space constraints, MBBR options would be more promising

- 1) To optimize the MBBR reactor by:
  - separating the aerobic process into two stages of BOD removal and nitrification;
  - raising the DO to 5 mg/L in the nitrification reactor and so increasing the nitrification rate;
  - increasing the media fill ratio to 67% or higher, in all bioreactors;
  - optimizing the volume-fractions and HRT proportions of the anoxic, BOD removal, and nitrification reactors so that the overall system can attain a shorter minimum HRT.
  
- 2) To improve the MBBR option treating raw sewage by pre-treatment using compact solids removal technology such as fine mesh sieve filters to removing particulate material.

# Thank You

## Q & A